

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
27 May 2004 (27.05.2004) ✓

PCT

(10) International Publication Number  
WO 2004/045046 A1 ✓

(51) International Patent Classification<sup>7</sup>: H02J 11/00

(74) Agent: ABB AB; Legal & Compliance/ Intellectual Prop-  
erty, Forskargränd 8, S-721 78 Västerås (SE).

(21) International Application Number:  
PCT/SE2003/001731

(81) Designated States (*national*): AE, AG, AI, AM, AT (util-  
ity model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA,  
CH, CN, CO, CR, CU, CZ (utility model), DE (util-  
ity model), DK (utility model), DK, DM, DZ, EC, EE  
(utility model), EE, EG, ES, FI (utility model), FI, GB, GD,  
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,  
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,  
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,  
SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(22) International Filing Date:  
10 November 2003 (10.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0203374-4 13 November 2002 (13.11.2002) SE

(71) Applicant (*for all designated States except US*): ABB AB  
[SI/SE]; Kopparbergsvägen 2, S-721 83 Västerås (SE).


(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

(72) Inventor: and

(75) Inventor/Applicant (*for US only*): ÅNGQUIST, Lennart  
[SI/SE]; Åsundavägen 26, S-745 71 Enköping (SE).

[Continued on next page]

(54) Title: AUXILIARY POWER SUPPLY



(57) Abstract: An auxiliary power supply equipment for a high voltage installation 1, 7, 8 has a power source 3 at ground potential, a load circuit 4 at high potential, and a transmission link 5, 6 for coupling the power source to the load circuit. The power source comprises a high frequency voltage generator 31, and the transmission link comprises a first 5 and a second 6 current path. Each path is closed by capacitive coupling 51, 61, 61' to provide insulation between the ground potential and the high potential, and each current path has a reactive compensation means 52, 62, 312, 63, 313, 62', 53', 412', 63', 413 for series compensation of reactive power generated by the capacitive coupling.



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*